



> PRINT > COPY > SCAN > FAX

ECOSYS M6030cdn
ECOSYS M6530cdn

COLOUR MULTIFUNCTIONALS
FOR A4 FORMAT

FLEXIBLE TEAM
PLAYERS.



These productive multifunctional devices offer fast print speeds and a short wait for the first copy. Their high input capacity and exceptional scanning performance make large digitisation projects a breeze. And thanks to their minimum downtime – based on the KYOCERA long-life components – plus full duplex support, they are ideal for busy, environmentally aware offices.

- > Up to 30 pages per minute in A4 in colour and b/w
- > Up to 9,600 dpi printing quality with multi-bit technology
- > Double-sided print, copy, scan and fax* functionality as standard
- > 75 sheet reversing document processor with support of A6 scan
- > Advanced scan functionality with compact and encrypted PDF
- > Up to 5 input trays for various media types
- > Mobile printing support including AirPrint, Mopria, KYOCERA Mobile Print
- > Exceptionally low printing costs in its class

*Only ECOSYS M6530cdn



ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means the toner is the only consumable for the first 200,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility.

**ECOSYS M6030cdn | ECOSYS M6530cdn
GENERAL**

Technology: KYOCERA ECOSYS, Colour Laser
Control panel display: 5 lines LCD display
Engine speed: Up to 30 pages A4 per minute in colour and b/w
Resolution: 600 x 600 dpi, multitbit technology for print quality of up to 9,600 x 600 dpi (print), 600 x 600 dpi, 256 greyscales per colour (scan / copy)
Duty cycle: Max. 100,000 pages per month
Warm-up time: Approx. 26 seconds or less
Time to first print: Approx. 7 / 8.5 seconds or less in b/w / colour
Time to first copy: Approx. 9.5 / 11.5 seconds or less in b/w / colour
CPU: PowerPC 465S / 1 GHz
Memory: Standard 1,024 MB, max. 2,048 MB
Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT) Slot for optional internal print server or SSD hard disc Slot for optional SD/SDHC-Card
Integrated accounting: 100 department codes
Dimensions (W x D x H): Main unit: 475 x 558 x 616 mm
Weight: Main unit: Approx. 34.6 / 34.7 kg
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption:
 Copy / Print: 510 W / 502 W
 Ready mode: 57 W
 Sleep mode: 2.1 W
Noise (Sound pressure level: ISO 7779 / ISO 9296):

ECOSYS M6030cdn ECOSYS M6530cdn

Copy / Print colour: 48.4 dB(A) LpA 48.7 dB(A) LpA
 Quite mode in colour: 46.2 dB(A) LpA 46.6 dB(A) LpA
 Sleep mode: Immeasurably low

Safety standards: GS, TÜV, CE
 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray: 60 – 220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – 216 x 356 mm) 250-sheet universal cassette: 60 – 163 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 – 216 x 356 mm). Max. input capacity with options: 1,850 sheets

Duplex functionality as standard: Double-sided printing: 60 – 163 g/m²; A4, A5, B5, Letter, Legal

Reversing document processor: 75-sheet, 50 – 120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 to 216 x 356 mm)

Output capacity: Max. 250 sheets face-down with paper full sensor

PRINT FUNCTIONS

Control language: PRESCRIBE IIc
Emulations: PCL 6 (PCL 5c/PCL-XL), PostScript 3 (KPLD 3), PDF Direct Print 1.7, XPS Direct Print
Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

COPY FUNCTIONS

Max. original size: A4 / Legal
Continuous copying: 1-999
Zoom range: 25–400 % in 1 % steps
Pre-set magnification ratios: 7 Reductions / 5 Enlargements
Exposure mode: Auto, manual: 9 steps
Image adjustments: Text + Photo, Photo, Text, Map, Printed document
Features: Auto Colour Mode, Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail (SMTP over SSL), Scan-to-FTP (FTP over SSL), Scan-to-SMB, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network)
Scan speed: 40 ipm (300 dpi, A4, b/w), 30 ipm (600 dpi, A4 b/w, 300 dpi, A4, colour)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales-per colour)
Max. scan size: A4, Legal
Original recognition: Text + Photo, Photo, Text, Light Text/ Fine Line, Text (for OCR)
File types: TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS
Compression method: MMR / JPEG
Features: Integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB / FTP folder, print) at once

FAX FUNCTIONS (ECOSYS M6530cdn only)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Less than 3 seconds
Scanning speed: 2.5 seconds
One-touch dial: 22 numbers
Address book: 200 entries
Scanning density: Normal: 200 x 100 dpi, Fine: 200 x 200 dpi

Superfine: 200 x 400 dpi, Ultrafine: 400 x 400 dpi
 Halftone: 256 greyscales

Maximum original size: A4, Legal
Compression method: JBIG, MMR, MR, MH
Memory reception: 256 sheets or more
Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

OPTIONS

PF-5100 Paper feeder (max 3 units): Max. 500 sheets; 60–220 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm to 216 x 356 mm)
MS-5100 Convenient Stapler: 20 sheets, one position semi-automatic stapling, includes 1,500 staples
CB-5100H Cabinet: Wooden desk with storage capacity. Approx. 39 cm x 53 cm x 50 cm (WxDxH)
CB-5100L Cabinet: Wooden desk with storage capacity. Approx. 39 cm x 53 cm x 37 cm (WxDxH)
Memory upgrade: MDDR3-1GB: 1.024 MB
HD-6 SSD: 32 GB for easy document management
HD-7 SSD: 128 GB for easy document management
Data security kit (E): in line with security level EAL3
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available
UG-33: ThinPrint support

Optional interfaces:
IB-50 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)
IB-51 Wireless LAN: 802.11b/g/n

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798
Toner-Kit TK-5140C, TK-5140M, TK-5140Y: cyan, magenta, yellow toner yield 5,000 pages A4
 Starter toner: cyan, magenta, yellow toner yield 2,500 pages A4
Toner-Kit TK-5140K: black toner yield 7,000 pages A4
 Starter toner: black toner yield 3,500 pages A4
SH-13 Staple cartridge: 2 x 1,500 staples for MS-5100

WARRANTY

1-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 200,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYOLIFE The up to 5-year on-site warranty extension for printer and options.



April 2015/ECOSYS M6030cdn/M6530cdn/EMC



Официальный дистрибьютор Kyocera в Украине
 01054, г. Киев, ул. Гончара, 36-А
 (044) 234-33-46, 234-33-26
 www.kyocera.kiev.ua
 info@kyocera.kiev.ua

KYOCERA Document Solutions Europe B.V. – Branch Office Germany
 Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany
 Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100
 www.kyoceradocumentsolutions.eu – info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri
 Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country

YOUR KYOCERA BUSINESS PARTNER

