


# Powering productivity

Durable, efficient, and built to last, the ECOSYS PA2101cx/PA2101cwx is the perfect fit for your home office, facilitating smoother remote collaboration with cloud connectivity and mobile print functionality.



**ECOSYS PA2101cx/PA2101cwx**

**A4 colour printer**

**Up to 21 pages per minute**

**Simple user interface**

## Specifications

### GENERAL

KYOCERA ECOSYS Laser Colour Printer

**Operation panel:** Colour 2.7inch TFT

**Type:** Desktop

**Engine speed:**

Up to 21 A4 pages per minute simplex (single-sided),

Up to 11 A4 pages per minute duplex (both sides)

**Resolution:** 1200 x 1200 dpi

**Recommended Print Volume:** Average 600 images per month

**Maximum Print Volume:** 65,000 pages per month

**Maximum Life:** 100,000 pages or 5 years

**Warm-up time:** Approx. 32 seconds or less (after switching on)

**Time to first print:** Approx. 11/12.5 seconds or less b/w/colour

**CPU:** ARM Cortex-A53 single core 1.0GHz

**Memory:** Standard 1 GB

**Standard interfaces:** USB 2.0 (Hi-Speed), Network (10BASE-T/100BASE-TX/1000BASE-T), WLAN (802.11a/b/g/n/ac, Wi-Fi Direct, 2.4/5 GHz)<sup>2</sup>, USB host for USB flash memory, IC Card Reader, slot for optional SD/SDHC card

**Integrated accounting:** 20 department codes

**Dimensions (W x D x H):**

Without packaging: 410 x 410 x 329 mm,

With packaging: 596 x 571 x 459mm

**Weight:** Without packaging:

Approx. 22 kg (with bundled toner)

Approx. 21 kg (without bundled toner)

With packaging: 28 kg

**Power source:** AC 220 ~ 240 V, 50/60 Hz

**Power consumption:**

Printing: 345 W

Ready mode: 33 W

Sleep-mode: 0.3 W

**Noise (sound pressure level: ISO 7779/ISO 9296):**

Printing: 48 dB(A)

Quiet mode: 44 dB(A)

Stand-by: 30 dB(A)

**Safety standards:** TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

### PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

**Input capacity:** Multi-purpose tray: 50 sheets, 60–220 g/m<sup>2</sup>, A6, A5, A4, custom (70 × 148 – 216 × 356 mm),

Standard universal paper cassette: 250 sheets, 60–163 g/m<sup>2</sup>,

A6, A5, A4, custom (100 × 148 – 216 × 356 mm),

Max. input capacity with options: 550 sheets.

**Duplex:** Standard duplex unit, two-sided printing, 60–120 g/m<sup>2</sup>, A5, A4, custom (140 × 210 - 216 × 356 mm).

**Output capacity:** Max. 150 sheets (face-down)

### PRINT FUNCTIONS

**Controller language:** PRESCRIBE

**Emulations:** PCL 6 (5c, XL), KPDL3 (PostScript 3 compatible),

PDF Direct Print 1.7, 2.0, XPS/Open XPS Direct Print,

TIFF Direct Print

**Operating systems:** All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, as well as other operating systems on request

**Fonts/barcodes:** 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bimap font, 45 one-dimensional barcodes (e.g. EAN-8, EAN-13, EAN-128), as well as support for two-dimensional barcodes PDF417 under PRESCRIBE (PCL and other barcodes available an option)

**Print features:** "Proof and hold"<sup>3</sup>, Job storage<sup>3</sup>, Quick copy<sup>3</sup>, Private print<sup>3</sup>, Data storage method with PIN code or password<sup>3</sup>, Internet printing IPP 1.0, E-mail printing,

WSD Print, EcoPrint - toner save mode, AirPrint, Mopria,

Microsoft Universal Print, Job batch output, Kyocera Image Refinement, Pull print, VPSX, IPP PIN Print, Kyocera Cloud

Access, optional Kyocera Cloud Print and Scan, Secure Boot, Run-time Integrity Check, Allowlisting, TLS 1.3,

IPSec, HTTPS, SNMPv3, S/MIME, encrypted PDF direct printing, Security Watermark, electronic PDF signature,

IPP over TLS, WSD, local and network authentication,

Windows authentication (NTLM v2, Kerberos), Restriction of the user group through user login administration, IP

filtering, port number restriction, blocking of interfaces,

Security Quick Setup, Administrator Authentication on

Firmware Update, SIEM Support (SysLog), SCEP, OCSP/

CRL, optional TPM (Trusted Platform Module)

**Mobile printing support:** KYOCERA Mobile

Print app for iOS and Android, AirPrint, Mopria,

Microsoft Universal Print, Wi-Fi Direct<sup>4</sup>

### CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798

**TK-5480K Toner Kit:**

Microfine toner black for 1,250 pages A4.

Capacity of starter toner is 1,500 pages A4.

**TK-5480C, TK-5480M, TK-5480Y Toner Kit:**

Microfine toner cyan, magenta, yellow for 1,250 pages A4

Starter toner cyan, magenta, yellow toner yield 1,500 pages A4

**TK-5490K Toner Kit:**

Microfine toner black for 2,800 pages A4.

**TK-5490C, TK-5490M, TK-5490Y Toner Kit:**

Microfine toner cyan, magenta, yellow for 2,400 pages A4

### OPTIONS

**PF-5110 Paper feeder (max. 1 units):**

Max. 250 sheets, 60 – 163 g/m<sup>2</sup>; A6, A5, A4, custom (105 mm × 148 mm – 216mm × 356mm)

### SECURITY

**UG-33:** ThinPrint support

**UG-51:** TPM (Trusted Platform Module), additional protection of confidential data

**USB IC Card Reader + Card Authentication Kit (B):** Support for various authentication keys available

### WARRANTY

1-year warranty as standard<sup>4</sup>.

### KYOCERA LIFE

Up to 5-year on-site warranty extensions available for product and options.

### WHAT'S IN THE BOX:

Main unit, starter toner for 1,500 pages Black, Cyan, Magenta, Yellow, Quick Guide, safety instructions, power supply cord.

DVD with drivers, software and user manual not contain. Computer with internet connection for download the drivers and software required.

<sup>1</sup> The device is not designed to achieve the specified volumes in continuous operation.

<sup>2</sup> Only ECOSYS PA2101cwx

<sup>3</sup> Optional SD/SDHC memory card is required

<sup>4</sup> Depending on the country

ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.



KYOCERA Document Solutions Partner

KYOCERA Document Solutions Europe Management B.V.  
Beechavenue 27, 1119 RA, Schiphol-Rijk – The Netherlands  
Tel +31 (0) 20-654-0000 – Fax +31 (0) 20-653-1256  
www.kyoceradocumentsolutions.eu – info@deu.kyocera.com



\* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.